

**REMARKS**

This Preliminary Amendment is submitted to improve the form of the English translation as filed. It is respectfully requested that this Preliminary Amendment be entered in the above-referenced application.

In accordance with the foregoing, claims 1-15 have been canceled and claims 16-30 have been added. Thus, claims 16-30 are pending and are under consideration.

A substitute specification is also being filed herewith. The substitute specification is accompanied by a marked-up copy of the original specification. No new matter has been added.

If there are any questions regarding these matters, such questions can be addressed by telephone to the undersigned. Otherwise, an early action on the merits is respectfully solicited.

If there are any additional fees associated with filing of this Preliminary Amendment, please charge the same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY LLP

Date: 5/15/06

By: Richard A. Gollhofer  
Richard A. Gollhofer  
Registration No. 31,106

1201 New York Ave, N.W., 7th Floor  
Washington, D.C. 20005  
Telephone: (202) 434-1500  
Facsimile: (202) 434-1501

Serial No.:

**IN THE ABSTRACT:**

Please DELETE the Abstract in its entirety and substitute the attached new Abstract.

Serial No.:

**IN THE SPECIFICATION:**

Please REPLACE the pending specification with the substitute specification attached hereto.

## MARKED-UP SUBSTITUTE SPECIFICATION

### Description-TITLE OF THE INVENTION

ESTABLISHMENT OF [[A]] TRANSCODER-FREE OPERATION CONNECTION

### CROSS REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is based on and hereby claims priority to German Application No. 10 2004 019 987.6 filed on April 23, 2004, the contents of which are hereby incorporated by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

**[0002]** The invention relates to a method and device for establishing a transcoder-free operation connection (TrFO) between two communication terminals (MS) in a communication network.

#### 2. Description of the Related Art

**[0003]** In order to use transcoder-free operations (TrFO), a common codec type or in the case of a multi-rate codec type a common set or common configuration of codec modes has to be negotiated between the network units (UEs, RNCs, MSCs) involved. To this end, a switching unit (MSC) has access to a storage unit containing information about the radio network controller (RNC). The storage unit for example contains an input specifying the codec modes supported by the access network (UTRAN) or the radio network controller (RNC). This storage unit is downloaded by the operator for each O&M (operation and maintenance) device and contains a list of the codec modes.

**[0004]** However the access network UTRAN with radio network controllers RNC only supports quite specific combinations of codec modes. It would be too complex to support all codec modes in all combinations and would take up a large number of resources. The information required to negotiate the codec mode to be used for the transcoder-free operation is exchanged between the communication terminals (MSs) and switching units (MSCs) at the lu interface by means of NAS signaling or at the Nc interface by means of BICC signaling.

**[0005]** According to the content of the storage unit, a radio network controller RNC 1 for example supports the codec modes a, b, c, d, f in the combinations (codec mode configuration) a/b and b/c/d/f. The supported codec mode configurations have to be taken into account when negotiating the codec modes. Currently only individual codec modes are negotiated, not codec mode configurations, which each ~~comprise~~ includes a number of codec modes. This means that it is sometimes not possible to establish a TrFO connection, as with the plurality of possible codec mode configurations (15 codec mode configurations are currently defined), it is very probable that the two radio network controllers RNCs involved in negotiating a TrFO connection support an overlapping number of identical modes but only in different codec mode configurations. If the radio network controller RNC2 supports the code mode configurations "a/b/c" and "f/g/h" for example, it is currently not possible to establish a transcoder-free operation connection between the radio network controller RNC1, which supports a/b and b/c/d/f, and the radio network controller RNC2.

#### SUMMARY OF THE INVENTION

**[0006]** ~~The object~~ An aspect of the present invention is therefore to provide a simple and effective ~~means way~~ way of increasing the probability that a transcoder-free operation connection can be established between two communication terminals. ~~According to the invention this object is achieved respectively by the subject matter of the independent claims. Developments of the invention are set out in the subclaims.~~

**[0007]** ~~The essence of the invention is that, in~~ In the event of a request from a switching unit relating to the use of at least one subset of a codec mode configuration for the establishment of a transcoder-free operation connection, a radio network controller, which supports all the subsets of a supported codec mode configuration, checks whether the at least one requested subset is supported. Such a subset ~~comprises~~ includes at least one, preferably at least two codec modes of a codec mode configuration but fewer than all the codec modes of the codec mode configuration. A transcoder-free operation connection is then established, if the result of the check is that at least this one subset is supported. To ensure compatibility with the lu interface, the radio network controller signals to the communication terminal ~~by means of~~ using a suitable message that data should only be sent in the uplink direction (from the communication terminal to the radio network controller) with the at least one supported subset of a codec mode configuration, as requested by the switching unit. One advantage of the

invention is that the probability of a transcoder-free operation connection being set up between two communication terminals can be increased significantly in a simple and effective manner.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0008]** ~~The~~ These and other objects and advantages of the present invention is described in will become more detail below with reference to apparent and more readily appreciated from the following description of an exemplary embodiment illustrated in a figure, taken in conjunction with the accompanying drawings of which:

Figure 1 ~~shows~~ is a block diagram of a simplified network architecture for the known negotiation of a codec mode for a connection between two communication terminals,

Figure 2 ~~shows~~ is a block diagram of a simplified network architecture for the claimed method according to an aspect of the invention, and

Figure 3 ~~shows~~ is a block diagram of a claimed device for implementing the method illustrated in Figure 2.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

**[0009]** Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout.

**[0010]** Figure 1 shows a simplified network architecture for negotiating a codec mode for a connection between two communication terminals UE in for example a cellular mobile radio network, such as the UMTS network. The radio network controller RNC1 supports two different codec mode configurations (mode 1, 2 and mode 3, 4). In contrast all AMR modes 1 to 4 are input in the RNC1 storage unit T1 of the controlling switching unit MSC1. The codec mode configurations supported by the radio network controller RNC1 are not taken into account. The second radio network controller RNC2 also supports two different codec mode configurations (mode 1, 2 and mode 4, 5). In the RNC2 storage unit T2 of the second switching unit MSC2 the codec mode configurations in the radio network controller RNC2 are in turn not taken into account. All AMR modes 1 to 5 are again input in the RNC2 storage unit T2. For codec negotiation the sending (originating) side with the switching unit MSC1, the RNC1 storage unit T1 and the radio network controller RNC1 transmits all supported codec types and modes, for example in the form of a list, table, etc., to the receiving (terminating) side with the switching unit MSC2, the RNC2 storage unit T2 and the radio network controller RNC2 (1). On the receiving

side this list, table, etc. of supported codec types and modes is reduced by the types and modes that are not supported on the receiving side, one codec mode is selected with one codec mode configuration and sent back to the sending side (2). RAB (Radio Access Bearer) assignment is now initiated with the selected codec mode in the direction of the radio network controller RNC1 (3). As the radio network controllers RNC1 and RNC2 do not however support the selected codec mode configuration (1, 2, 4), the RAB assignment is rejected (4). A connection with a transcoder-free operation cannot therefore be set up between two communication terminals UE, for example mobile radio terminals, mobile computers, mobile organizers, etc.

**[0011]** Figure 2 ~~describes the claimed~~ shows a method according to an aspect of the invention in a communication network, preferably a cellular mobile radio network. If a radio network controller RNC receives a request relating to the use of a subset (for example a/b) of a codec mode configuration (for example a/b/c) for the establishment of a transcoder-free operation connection between two communication terminals, MS, it (RNC) checks whether the requested subset a/b is supported. The request can be sent in the form of a RAB (Radio Access Bearer) request from the switching unit MSC to the radio network controller RNC. If the requested subset is supported by the radio network controller RNC, a connection, e.g. a RAB (Radio Access Bearer) connection, is established to the switching unit MSC using the requested subset a/b of a codec mode configuration. A connection is established to an air interface or to the communication terminal MS from the radio network controller RNC using the codec mode configuration a/b/c, as the radio network controller has only stored all the necessary data (e.g. transport formats, SIR targets, etc.) for the codec mode configuration. However to ensure compatibility with the lu interface, on which mode c is not permitted, the radio network controller RNC uses a signaling message, for example a Transport Combination Control Message TCCM, a radio resource control signaling, etc., to restrict the codec mode configuration to a permitted subset a/b negotiated with the switching unit. The signaling message or messages can also be signaled to the communication terminal MS in a number of parts or steps. Thus in a first step or part of the signaling message the codec mode configuration to be used with at least two codec modes could be transmitted to the communication terminal MS and in a second step or part of a signaling message the subset of a codec mode configuration to be used could be notified to the communication terminal MS. When using a codec mode, the communication terminal MS must restrict itself to the signaled subset. In this example, when data is sent in the uplink direction, the communication terminal can only use modes a and/or b. With this method it is then possible to increase significantly the probability of setting up a TrFO connection between two

communication terminals MS, as the access network UTRAN with for example radio network controllers RNC can support not only codec mode configurations but also their subsets, thereby enhancing the quality of the service considerably.

**[0012]** Figure 3 shows a ~~claimed device~~ for implementing the method, ~~as described~~ shown in Figure 2. The device, ideally a radio network controller RNC, has a send unit (S) and a receive unit (E) for mobile communication with further network units (MS, MSC). A processing unit (V) in the radio network controller RNC is used to check a request sent from a switching unit MSC relating to the use of a subset of a codec mode configuration for the establishment of a transcoder-free operation connection between two communication terminals MS. Moreover the processing unit establishes a connection both to the requesting switching unit MSC and to the communication terminal, if the requested subset is supported. A signaling message is also sent from the processing unit (V) via the send unit (S) to the communication terminal MS relating to the subset of the codec mode configuration to be used to transmit data to the radio network controller.

**[0013]** The invention has been described in detail with particular reference to preferred embodiments thereof and examples, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention covered by the claims which may include the phrase "at least one of A, B and C" as an alternative expression that means one or more of A, B and C may be used, contrary to the holding in *Superguide v. DIRECTV*, 69 USPQ2d 1865 (Fed. Cir. 2004).